Inductor Data Sheet

LQM21NNR10K10#

"#" indicates a package specification code.

In Production | General | 85 °C max. | Multi-layer | Reflow OK | Flow OK | RoHS | REACH

< List of part numbers with package codes >
LQM21NNR10K10D , LQM21NNR10K10J , LQM21NNR10K10B

Shape



Dimension of t		
	Inductance: 0.1 to 2.2μH	0.85±0.2
	Inductance: 2.7 to 4.7μH	1.25±0.2

L size	2.0 ±0.2mm
W size	1.25 ±0.2mm
T size	0.85 ±0.2mm
Size code in inch (mm)	0805 (2012)

References

Packaging code	Specifications	Minimum quantity
D	φ180mm Paper taping	4000
J	φ330mm Paper taping	10000
B	Packing in bulk	1000

Mass (Typ.)	
1 piece	0.010g

Specifications

Inductance	0.10μH ±10%
Inductance test frequency	25MHz
Rated current (Isat) (Based on Inductance change)	250mA
Rated current (Itemp) (Based on Temperature rise)	250mA
Max. of DC resistance	0.26Ω
Q (min.)	20
Q test frequency	25MHz
Self resonance frequency (min.)	340MHz
Operating temperature range (Self-temperature rise is not included)	-40°C to 85°C
Class of magnetic shield	Ferrite Core
Series	LQM21NN_10

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)

- Inductance-Current characteristics (Typ.)



- Q-Frequency characteristics (Typ.)



Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.