



**Specifications:**

Contact Resistance: 30mΩ max.at DC 100 mA  
 Insulator Resistance: 1000MΩ min.at DC 500V  
 Current Rating: 1AMP

**Dielectric Withstanding**

Voltage: AC 500V For 1 minute  
 Operating Temperature:-55°C--+105°C

Contact: Phosphor bronze

Housing: PPS & 40% Glass Fiber (UL 94V-0)

PBT & 30% Glass Fiber (UL 94V-0)

Position	A	B	C	D
28	7.62	18.10	22.20	12.70
32	7.62	18.80	25.70	12.70
32	10.16	21.30	25.70	15.24
44	12.70	23.50	29.80	17.78
52	15.24	26.00	32.64	20.32
68	20.32	30.20	40.10	25.40
84	25.40	35.20	46.90	30.48

**要求:**

1. 塑料件无裂痕。
2. 整排针成一直线，相邻针之间相互平行。

设计/Designed by	绘图/Drawing by	审核/Checked by	批准/Approved by	未注公差 General Tolerance	
				x. ±0.2	x.' ±2°
				.x ±0.1	.x' ±1°
				.xx ±0.05	.xx' ±0.5°
				.xxx ±0.01	
				单位/Units: <b>mm</b>	