

120X120X25 mm

JF1225-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)		
JF1225B1URAB	B	12	10.2 ~ 13.8	111.36	0.340	3200	0.50	6.00	0.50	47.8	205		
JF1225B1UR				100.50	0.269	3000	0.50	6.00	0.50	45.7			
JF1225B1SR				89.87	0.224	2700	0.37	4.44	0.37	42.8			
JF1225-1H	B, S			80.11	0.186	2400	0.25	3.00	0.30	39.5			
JF1225-1M	B, S			69.57	0.147	2100	0.20	2.40	0.25	36.3			
JF1225-1L	B, S			59.57	0.111	1800	0.14	1.68	0.20	32.4			
JF1225-1E	B, S			47.88	0.078	1500	0.10	1.20	0.12	27.4			
JF1225B2URAB	B			24	20.4 ~ 27.6	111.36	0.340	3200	0.28	6.72		0.28	47.8
JF1225B2UR						100.50	0.269	3000	0.28	6.72		0.28	45.7
JF1225B2SR						89.87	0.224	2700	0.21	5.04		0.21	42.8
JF1225-2H	B, S					80.11	0.186	2400	0.20	4.80		0.25	39.5
JF1225-2M	B, S					69.57	0.147	2100	0.14	3.36		0.20	36.3
JF1225-2L	B, S	59.57	0.111			1800	0.11	2.64	0.15	32.4			
JF1225-2E	B, S	47.88	0.078			1500	0.08	1.92	0.10	27.4			
JF1225B4UR	B	48	40.8 ~ 55.2			100.50	0.269	3000	0.14	6.72		0.14	45.7
JF1225B4SR						89.87	0.224	2700	0.12	5.76		0.12	42.8
JF1225B4HR						80.11	0.186	2400	0.10	4.80		0.10	39.5
JF1225B4MR						69.57	0.147	2100	0.08	3.84		0.08	36.3
JF1225B4LR						59.57	0.111	1800	0.07	3.36		0.07	32.4
JF1225B4ER				47.88	0.078	1500	0.06	2.88	0.06	27.4			

Specifications subject to change without notice

The 7TH character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM".

Please contact us for detail if your request bearing system is not shown in the above list.

