

## 120X120X38 mm

## JF1238-19 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

### SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH <sub>2</sub> O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF1238B1SR	B	12	10.2 ~ 13.8	135.8	0.356	3200	0.70	8.40	0.80	47.9	278
JF1238-1HR	B, S			118.7	0.281	2800	0.48	5.76	0.55	43.8	
JF1238-1MR	B, S			101.3	0.213	2400	0.32	3.96	0.38	39.1	
JF1238-1LR	B, S			84.5	0.155	2000	0.20	2.40	0.21	33.8	
JF1238-1ER	B, S			69.6	0.109	1700	0.10	1.20	0.11	29.6	
JF1238B2SR	B	24	20.4 ~ 27.6	135.8	0.356	3200	0.37	8.88	0.45	47.9	
JF1238-2HR	B, S			118.7	0.281	2800	0.31	7.44	0.32	43.8	
JF1238-2MR	B, S			101.3	0.213	2400	0.22	5.28	0.23	39.1	
JF1238-2LR	B, S			84.5	0.155	2000	0.13	3.12	0.14	33.8	
JF1238-2ER	B, S			69.6	0.109	1700	0.09	2.16	0.11	29.6	
JF1238B4SR	B	48	40.8 ~ 55.2	135.8	0.356	3200	0.20	9.60	0.22	47.9	
JF1238B4HR	B			118.7	0.281	2800	0.13	6.24	0.15	43.8	
JF1238B4MR	B			101.3	0.213	2400	0.09	4.32	0.11	39.1	
JF1238B4LR	B			84.5	0.155	2000	0.07	3.36	0.08	33.8	

Specifications subject to change without notice

The 7<sup>TH</sup> character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM". Please contact us for detail if your request bearing system is not shown in the above list.

