



Category: 直插式弹簧接线/Plug-in terminal-plug

Product name: TPK2.5-4-GY

Product Description: 5.2mm



Product Picture



基本信息 /Basic Information

产品型号 SUPU ID	TPK2.5-4-GY
宽度 Width	5.2mm
产品层数 Number of levels	1
接线位数 Number of connections	3
接线方式 Connection method	直插弹簧接线
防护等级 Protection Level	IP20

工作温度	-40~+105℃
Work temperature	

IEC数据 /IEC Data

额定电流	20A
Rated Current	
额定电压	400V
Rated Voltage	
过压类别	Ⅲ
Overvoltage category	
污染等级	3
Pollution degree	
额定冲击电压	6KV
Rated impulse voltage	
刚性导线截面积	0.2-4mm²
Conductor cross section solid	
柔性导线截面积	0.2-2.5mm²
Conductor cross section flexible	
柔性导线截面积，带绝缘管套	0.2-2.5mm²
Conductor cross section flexible,with furrule	
剥线长度	8-10mm
Stripping length	

UL数据 /UL Data

使用组别	B	C	D
Use group			
额定电流	20A	20A	-
Rated Current			
额定电压	300V	300V	-
Rated Voltage			
额定接线容量	26-12AWG		
Rated cross section			

材料信息 /Material Data

绝缘材料	PA66
Insulation material	
绝缘材料组别	I
Insulation material group	
阻燃等级，符合UL94	V0
Flame retardant grade, UL94	
compliance	

导电体材料 Contact material	Copper alloy
导电体表面镀层 Surface characteristics	Sn,Plated

产品认证 /Product Certification

认证图标 Certificate	
UL证书号 UL file No.	
VDE证书号 VDE No.	
TUV证书号 TUV No.	

包装信息 /Packing Data

包装信息 Packaging Information	100 pc
-------------------------------	--------

Ningbo Supu Electronics Co.,Ltd

Zip code: 315303

Fax: +86 574-63288170

E-mail : askme@supu.cn

Address: No. 625, Kandun Town Street, Cixi
City, Zhejiang Province

Switchboard: +86 574-63288158

E-mail : askme@supu.cn

Service Hotline: 400-626-6336



Code