



- NOTES:
1. Rating: 150V 5A;
  2. Insulation Withstands Voltage: AC1300V/MIN
  3. Insulation Resistance: 500MΩ or more at DC500V
  4. Using Temperature Range: -40°C~+105°C
  5. "★" is the important dimension.

Total Pitch Tolerances		Nominal dimension range	
in mm		in mm	
over	0	over	0
to	30	to	30
30	53	70	53
to	70	to	70
70	90	to	90
90	115	to	115
115	150	to	150
150	250	to	250
250	350	to	350
350	500	to	500
500	0	to	0
0	30	to	30
30	53	to	53
53	70	to	70
70	90	to	90
90	115	to	115
115	150	to	150
150	200	to	200
200	250	to	250
250	0	to	0
0	10	to	10
10	all	to	all
all	0	to	0
0	100	to	100
100	150	to	150
150	0	to	0
0	0.2	to	0.2
0.2	0.3	to	0.3
0.3	0.3	to	0.3
0.3	0.2	to	0.2
0.2	0.3	to	0.3
0.3	0.5	to	0.5
0.5		to	

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	ZX	DATE	2020.12.11	SIZE	A4
CHK.		DATE		SCALE	2:1
App.		DATE		NAME	KSE-15EDGVC-2.50-02P
			DWGNO.		

